



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

D350-636-012
Job Sheet 175060



Part No: D350-636-012

Job Qty: 1 ea

Part Name: Skidtube RH, Std Wearplates, DART (Apical) Cylindrical/Aerazur Float Comp.



Part Weight: 0 lbs

Status: Scheduled

Priority: Medium

Job Created: 3/27/18

Job Tracking No:

Due Date: 4/18/18

Created By: Michelle Gagnon-Donovan

Type: SOLD

Description:

Note: DWG D3492 REV E SHEET 1, D2750-042 REV G SHEETS 1,2,5,9 IPP Rev:I 02.09.25 IPP Rev:J 06-03-23 As per Rev D IPP Rev:K 06-07.13 As per dsi9343 IPP Rev:L 07-07-28 Added SS Wearplates(Rev E) JLM Verf:EC IPP Rev:M 08-04-22 DD verified:EC IPP Rev:N 08-09-23 revF DD verified:ec IPP Rev:O 09-02-06 per PAR09-010 DD verf:EC IPP Rev:P 10.06.22 revise seq110 DD verf:EC IPP Rev:Q 10.10.01 as per IIN revH DDverf:EC IPP REV:R 13.08.27 PER ECN13-594 DD VERF:JLM

Ship Via:

Bill of Materials



Dart Aerospace Ltd.
1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
CANADA
TEL.: 1 613 632-5200
Email: sales@dartaero.com
www.dartaerospace.com

Container No: S062270



Part: D350-636-012

Job No: 175060

Serial No/Batch: S062270

Revision:

Inspector:

Date: 04/18/18

S062270 R+1

art.Gagnon.Michelle

Job Routing									
Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Sign-off
					Setup hrs	Run Hrs	Workcenter / Supplier	Lead Time	
90	Start up Operation	1 Ea	4/17/18	4/17/18	0.00	0.00	Start Up Skid tubes-1		Mb
110	Skid tubes	1 pcs	4/17/18	4/17/18	0.00	4.36	Skid tubes-4		Mb
120	QC	1 pcs	4/17/18	4/17/18	0.00	0.00	QC10		38 DAS
130	QC	1 pcs	4/17/18	4/17/18	0.00	0.00	QC5		38 9-89
140	HandFinish	1 pcs	4/17/18	4/17/18	0.00	0.91	HandFinish1		SA 18-04-29
150	QC	1 pcs	4/17/18	4/17/18	0.00	0.00	QC7-2		38 DAS
160	Skid tubes	1 pcs	4/17/18	4/17/18	0.00	4.36	Skid tubes-1		38 DAS
170	QC	1 pcs	4/17/18	4/17/18	0.00	0.00	QC10		38 9-89
180	QC	1 pcs	4/17/18	4/17/18	0.00	0.00	QC5		38 9-89
190	HandFinish	1 pcs	4/17/18	4/17/18	0.00	0.91	HandFinish2		SA 18-05-03
200	Spray Paint	1 pcs	4/17/18	4/17/18	0.00	0.69	Spray Paint		38 DAS
205	Outsource	1 pcs	4/17/18	4/17/18			ATE003-VC 39794		CY 18/05/04
210	QC	1 pcs	4/17/18	4/17/18	0.00	0.00	QC14		18-5-14
230	HandFinish	1 pcs	4/18/18	4/18/18	0.00	0.91	HandFinish4		BE 18-05-23
240	QC	1 pcs	4/18/18	4/18/18	0.00	0.00	QC5		38
250	Packaging	1 pcs	4/18/18	4/18/18	0.00	0.00	Packaging1-3		MAY 23 2018
260	QC	1 pcs	4/18/18	4/18/18	0.00	0.00	QC4		
265	DC	1 pcs	4/18/18	4/18/18	0.00	0.00	DC		DAS
270	Packaging	1 pcs	4/18/18	4/18/18	0.00	0.00	Packaging3-1		21
280	QC21-FG	1 Ea	4/18/18	4/18/18	0.00	0.00	QC21		9-89 MAY 23 2018

Part Op 110 - 1- Pick D2600-3 Bent Drill pilot holes as per Dwg D2750 sheet 4 (D2750-2 details). Drill using drill Jig DT8150 & Descriptions: DT8863A for second side only DT8863B for first side (detail K) 4- Locate DT8329 off of blade fitting bolt holes and drill pilot holes for blade fitting. Open to 0.500" using hole saw. VERIFY AND RECORD FWD BEND ANGLE. 6- Drill pilot holes for wearplates as per Dwg D2750 using DT8108 open to 0.297". 7- Open up holes of Detail J to 0.297" (total of 2 holes per side) 8- Weld D2744 Cap as per Dwg D2750 and QSI 004. Fill grooves in bend left from bending as per QSI 004 9- Grind welds flush as per Dwg D2750

160 - 1- Open up holes of Detail L using hole saw and ground handling to 0.625" (total of 8 holes per side) as per dwg D2750. 2- Open up holes of Detail K using hole saw to 0.750" (total of 4 holes per side) as per dwg D2750. 3- Open float holes using uni-bit to .500" (4 per Side) 4- Chamfer holes of Detail K, L, ground handling and float holes per dwg D2750 (welding instructions on sheet 9) 5- Deburr and blow out all chips from inside of tube 6- Prepare tube for welding, remove alodine as required. 7- Bond web D2739 in place as per QSI 015, let cure for 12hrs. A/R Sikaflex-291 batch: 18664 exp. date: 2018-01-21 **ATTN: USE I-BEAM LOCATION AID (BLADE FITTING)** 8- Weld spacers D3490-1, D3490-3 and D2743 as per dwg D2750 & QSI004 (welding instructions on sheet 9) A/R Aluminum Rod batch: 038011 9- At section AP-AP drill out x-bolt spacer to 0.404" 10-Grind welds flush as per Dwg D2750 11- Spot face ground handling holes section (total of 4 places per side) as per dwg D2750 12- Deburr holes, ensure tube is free of all scratches before sending to paint.

180 - ***VERIFY C'BOARD IS GOOD***

190 - Re-alodine tube as per QSI 005 section 4.1.2.1 do not acid etch.

200 - 1- PRIME AS PER DWG AND QSI 005 4.2 PRIMER PRC DESOTO 515X349 BATCH: _____ 2- PAINT WHITE AS PER DWG AND QSI 005 4.2 PAINT BATCH: _____

210 - Inspect for foreign object per QSI 024

230 - 1-Install inserts as per dwg D2750 2-Inspect for Foreign Objects 3-Install blade fitting D3488-042, wearshoes and ground handling hardware as per dwg D2750 SIKA FLEX 241 BATCH: _____ EXP DATE: _____ 4- assemble o'ring to plug as per dwg D3492 and apply o'ring lube A/R 55-o'ring lube batch: _____ 5-Coat all exposed fasteners with "LPS Procyon" batch: _____

265 - record fwd angle: 69.9 Photocopy blue file and type labels per PPP D350-636-012 CHG 007

270 - Package as per PPP D350-636-012

Job BOM

Part / Item	Component Name	Quantity	Operation	Container
D2600-3-BENT-RH	Extrusion Bent RH	1 Ea (1 ea)	90-Start up Operation	S 043928
D2744	Cap	1 Ea (1 ea)	90-Start up Operation	S 030835
D2739	350 I-Beam	1 Ea (1 ea)	160-Skidtubes	S 032813
D2743	Crossbolt Spacer	8 Ea (8 ea)	160-Skidtubes	S 032813 S 061803
D3490-1	Cross Bolt Spacer	4 Ea (4 ea)	160-Skidtubes	S 049269
D3490-3	Cross Bolt Spacer	4 Ea (4 ea)	160-Skidtubes	S 040318
ALS4-1032-225	Rivnut	38 Ea (38 ea)	230-HandFinish	S 058138
AN3C5A	Bolt	34 Ea (34 ea)	230-HandFinish	S 057153
AN3C6A	Bolt	4 Ea (4 ea)	230-HandFinish	S 019397
AN6C44A	Bolt	4 Ea (4 ea)	230-HandFinish	FM1133055
AN8C35A	Bolt	1 Ea (1 ea)	230-HandFinish	FM1137203
D2745	Bushing	8 Ea (8 ea)	230-HandFinish	S 053257
* D3488-042	Blade Fitting RH	1 Ea (1 ea)	230-HandFinish	* S 070890
D3492-1	Plug	8 Ea (8 ea)	230-HandFinish	S 052900
D3492-3	Plug	8 Ea (8 ea)	230-HandFinish	S 067012
D3535-25	Wearplate Center	1 Ea (1 ea)	230-HandFinish	S 060747
D3536-25	Gasket Center	1 Ea (1 ea)	230-HandFinish	S 059811
D3537-1	Wearpad	3 Ea (3 ea)	230-HandFinish	S 045654
D3631-1	Washer	8 Ea (8 ea)	230-HandFinish	S 058407
D3791-1	Wearpad	1 Ea (1 ea)	230-HandFinish	S 059894
* D3793-1	Wearplate Fwd	1 Ea (1 ea)	230-HandFinish	* S 070803
D3793-3	Wearplate Aft	1 Ea (1 ea)	230-HandFinish	S 043272
D3794-1	Gasket Fwd	1 Ea (1 ea)	230-HandFinish	S 059813
D3794-3	Gasket Aft	1 Ea (1 ea)	230-HandFinish	S 046513
MS21043-6	Nut	4 Ea (4 ea)	230-HandFinish	S 053037
MS21083C8	Nut	1 Ea (1 ea)	230-HandFinish	S 073370 S 034401
NAS1149C0332R	Washer	38 Ea (38 ea)	230-HandFinish	S 041236
NAS1149C0832R	Washer	1 Ea (1 ea)	230-HandFinish	M138409-12
NAS1515H3L	Washer	4 Ea (4 ea)	230-HandFinish	S 036714
NAS1611-010	O-Ring	8 Ea (8 ea)	230-HandFinish	S 062208
NAS1611-013	O-Ring	8 Ea (8 ea)	230-HandFinish	S 034467
AN8C21A	Bolt	2 Ea (2 ea)	250-Packaging	FM1137162
D2741	Replacement Blade	1 Ea (1 ea)	250-Packaging	S 040883
D3493-1	Washer	2 Ea (2 ea)	250-Packaging	S 052854
D3532-1	Spacer	2 Ea (2 ea)	250-Packaging	S 040493
MS21083C8	Nut	2 Ea (2 ea)	250-Packaging	S 050046
NAS1149D0863J	Washer	2 Ea (2 ea)	250-Packaging	F125635

003349

Job Allocations

Operation	Component Part	Required	Inventory	Allocated
90-Start up Operation	D2600-3-BENT-RH	1	8	0
	D2744	1	15	0
	D2739	1	25	0
160-Skidtubes	D2743	8	201	0
	D3490-1	4	64	0
	D3490-3	4	47	0
	ALS4-1032-225	38	1,026	0
	AN3C5A	34	87	0
230-HandFinish	AN3C6A	4	318	0
	AN6C44A	4	395	0
	AN8C35A	1	60	0
	D2745	8	201	0
	D3488-042	1	6	0
	D3492-1	8	187	0
	D3492-3	8	109	0
	D3535-25	1	17	0
	D3536-25	1	27	0
	D3537-1	3	144	0
	D3631-1	8	35	0
	D3791-1	1	13	0
	D3793-1	1	17	0
	D3793-3	1	25	0
	D3794-1	1	10	0
	D3794-3	1	38	0
	MS21043-6	4	170	0
	MS21083C8	1	166	0
	NAS1149C0332R	38	4,644	0
	NAS1149C0832R	1	85	0
	NAS1515H3L	4	243	0
	NAS1611-010	8	365	0
	NAS1611-013	8	261	0
250-Packaging	AN8C21A	2	141	0
	D2741	1	65	0
	D3493-1	2	60	0
	D3532-1	2	38	0
	MS21083C8	2	166	0
	NAS1149D0863J	2	147	0

Part Specifications

Specifications could not be found.

Plex 3/27/18 9:54 AM Dart.Gagnon.Michelle

QTY -041	QTY -042	QTY -043	QTY -044	PART NUMBER	DESCRIPTION
X				D2750-041	350 SKIDTUBE ASSEMBLY, LH
	X			D2750-042	350 SKIDTUBE ASSEMBLY, RH
		X		D2750-043	350 SKIDTUBE ASSEMBLY, LH
			X	D2750-044	350 SKIDTUBE ASSEMBLY, RH
1	1	1	1	D2739	WEB
8	8	8	8	D2743	SPACER
1	1	1	1	D2744	CAP
8	8	8	8	D2745	BUSHING
1				D2750-1	SKIDTUBE WELDMENT, LH
	1			D2750-2	SKIDTUBE WELDMENT, RH
		1		D2750-3	SKIDTUBE WELDMENT, LH
			1	D2750-4	SKIDTUBE WELDMENT, RH
1		1		D3488-041	BLADE FITTING, LH
	1		1	D3488-042	BLADE FITTING, RH
4	4	4	4	D3490-1	SPACER
4	4			D3490-3	SPACER
		4	4	D3490-5	SPACER
8	8	8	8	D3492-041	PLUG ASSEMBLY
8	8			D3492-043	PLUG ASSEMBLY
		8	8	D3492-045	PLUG ASSEMBLY
1	1	1	1	D3535-25	WEARSHOE
1	1	1	1	D3536-25	GASKET
3	3	3	3	D3537-1	WEARPAD
8	8	8	8	D3631-1	WASHER
1	1	1	1	D3791-1	WEARPLATE
1	1	1	1	D3793-1	WEARSHOE
1	1	1	1	D3793-3	WEARSHOE
1	1	1	1	D3794-1	GASKET
1	1	1	1	D3794-3	GASKET
38	38	38	38	ALS4-1032-225	INSERT (OR ALS7-1032-225, AKS4-1032-225, AELS-1032-225)
34	34	34	34	AN3C5A	BOLT
4	4	4	4	AN3C8A	BOLT
4	4	4	4	AN8C44A	BOLT
1	1	1	1	AN8C35A	BOLT
38	38	38	38	AN960C10L	WASHER
1	1	1	1	AN960C816L	WASHER
4	4	4	4	MS21043-6	NUT
1	1	1	1	MS21083C8	NUT
4	4	4	4	NAS1515H3L	WASHER

GENERAL NOTES:

- MATERIAL: MAKE D2750-1/-2/-3/-4 FROM D2600-3 EXTRUSION (INITIAL LENGTH = 120.0).
- FINISH: ACID ETCH, ALODINE ASSEMBLY PER DART QSI 005 4.1 PRIOR TO INSTALLING D2739 WEB.
STANDARD: PRIME (REF. 4.2.1.3.3) AND PAINT WHITE PER DART QSI 005 4.2
OPTIONAL: POWDER COAT WHITE (REF. 4.3.5.1) PER DART QSI 005 4.3
BLACK ANTI-SKID PAINT AS INDICATED TO 1.0 ABOVE SKIDTUBE CENTER-LINE PER DART 005 4.4 (OPTIONAL).
- TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- UNITS: INCHES UNLESS OTHERWISE NOTED
- BREAK SHARP EDGES: N/A
- IDENTIFICATION: N/A
- WEIGHT: D2750-041/-042/-043/-044 = 26.5 LBS
- WELD PER DART QSI 004
- INSTALL ALS4-1032-225 INSERTS AFTER FINISH AS INDICATED. DRILL 'F' SIZE HOLES (Ø0.297) FOR WEARSHOE INSERTS
- FINAL CONFIGURATION SHOULD HAVE THE FOLLOWING MINIMUM MECHANICAL PROPERTIES:
MINIMUM YIELD TENSILE STRENGTH = 35 KSI
MINIMUM ULTIMATE TENSILE STRENGTH = 38 KSI
- COAT ALL EXPOSED FASTENERS WITH LPS LABORATORIES "LPS PROCYON" AFTER FINAL ASSEMBLY, CLEAN EXCESS OFF FINISH WITH MEK DEGREASER.
- SPACER AND PLUG INSTALLED SAME AS SECTION AJ-AJ EXCEPT HORIZONTAL
- SPACER AND PLUG INSTALLED SAME AS SECTION AP-AP EXCEPT HORIZONTAL

SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER
NO. 175000

MAR 27 2018

RELEASED
2013-08-13

G	CORRECTED TOLERANCE ON Ø0.500 THRU HOLE: IS +0.016/-0.000, WAS +0.100/-0.000 (ZN B3-4, B2-5); ADD VIEW TO CONTROL FWD BEND ORIENTATION (ZN D-1-4/-5-6/-7); UPDATED FINISH OPTIONS: INSIDE OF TUBE NO LONGER SPRAYED WITH LPS-3. REASON: PARTS-278 AND NCR13-2757	MB	13.07.11
F	INCORPORATE DSI 9413. QTY (3) D3537-1 WAS QTY (5) (ZN C8-1); D3791-1/-3 REPLACES D3536-13/-35 (ZN C8-1); D3794-1/-3 REPLACES D3536-13/-35 (ZN B8-1); ADD D3791-1 (ZN C8-1); WEARSHOE HOLES UNDER FWDRAFT SADDLE REMOVED (8 PL). WEARSHOE HARDWARE QTY UPDATED (ZN B8-1); D3488-041/-042 HARDWARE UPDATED (ZN C1-8, 9, 10, 11); ADD NOTE 12 AND 13 (ZN A6-1); REASON: REF. NCR 08-043	PH	06.07.16
E	CHANGE TO STAINLESS STEEL WEARPLATES. ADD RUBBER GASKETS; CHANGE INSERTS; ADD D3631-1; REMOVE QTY (38) NAS1515H3L; REMOVE QTY (10) NAS1515H8L; REMOVE D2741, QTY (2) AN960C816; REMOVE QTY (2) MS21083C8	CB	07.05.17
D	ADD HOLES AND SPACERS FOR APICAL FLOATS; INCORPORATE DEO 9133/9157	PH	06.01.05
C	ADD D2750-3/D2750-4; INCORPORATE D2738 AND D2740	CP	98.11.16
B	CHANGE MS24694-S293 TO AN8-16A	CP	98.09.01
A	NEW ISSUE	DS	98.04.16
REV.	DESCRIPTION	BY	DATE
DESIGN	MM		
DRAWN			
CHECKED			
MFG. APPR.			
APPROVED			
DE APPR.			
DATE	13.07.11		

DART AEROSPACE USA, INC.

KENT, WA

DRAWING NO.
D2750

REV. G

SHEET 1 OF 11

TITLE


350 SKIDTUBE ASSEMBLY

SCALE


NTS

COPYRIGHT © 1998 BY DART AEROSPACE USA, INC.

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.





D2750-041 350 SKIDTUBE ASSEMBLY, LH



D2750-042 350 SKIDTUBE ASSEMBLY, RH


RELEASED
2013-08-13
MD

DESIGN	MM	DART AEROSPACE USA, INC.	
DRAWN	<i>[Signature]</i>	KENT, WA	
CHECKED	<i>[Signature]</i>	DRAWING NO. D2750	REV. G
MFG. APPR.	<i>[Signature]</i>	SHEET 2 OF 11	
APPROVED	<i>[Signature]</i>	TITLE	SCALE
DE APPR.	<i>[Signature]</i>	350 SKIDTUBE ASSEMBLY	NTS
DATE	13.07.11	COPYRIGHT © 1998 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PROVIDED FOR INFORMATION AND IS NOT TO BE USED FOR REPRODUCTION OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF DART AEROSPACE USA, INC.	




OUTBD


MAX ALLOWABLE
TWIST ON FWD BEND
(VIEWED LOOKING FWD)




DETAIL J
SCALE 2X




DETAIL K
SCALE 2X




DETAIL L
SCALE 2X




DETAIL M
SCALE 2X




SECTION N-N
SCALE 3X, 2 PL



SECTION P-P
SCALE 3X, 17 PL



SECTION Q-Q
SCALE 3X, 4 PL



SECTION R-R
SCALE 3X, 4 PL

DESIGN	MM	DART AEROSPACE USA, INC.	
DRAWN		KENT, WA	
CHECKED		DRAWING NO. D2750	REV. G
MFG. APPR.		SHEET 5 OF 11	
APPROVED		TITLE	SCALE
DE APPR.		350 SKIDTUBE ASSEMBLY	
DATE	13.07.11	NTS	

COPYRIGHT © 1996 BY DART AEROSPACE USA, INC.
THIS DOCUMENT IS UNCLASSIFIED AND IS AVAILABLE TO THE PUBLIC. IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.

RELEASED
2013-08-13



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

PURCHASE ORDER **PO039794**

Supplier: ATE003-VC
Atelier Debosselage
358 Principale
Calumet
QC
J0V 1B0 Canada
Phone: 819 242 5633

PO No: PO039794
PO Date: 5/4/18
Due Date: 5/7/18
Purchase Order Revision:
Revision Date:
Ship-To Contact: Lavoie, Chantal
Phone: clavoie@dartaero.com

Ship To: 1270 Aberdeen Street
Hawkesbury
ON
K6A 1K7 Canada
Phone: 613-632-5200

Via: Ground
Pynt Terms: Net 30
Freight Terms:
Special Comments:

Items

Line Item	Job	Part	Description	Status	Due Date	Order Quantity	Received Quantity	Balance	Unit Price (CAD)	Extended Price
1	175051	D350-636-011	Skidtube LH, Std Wearplates, DART (Apical) Cylindrical/Aerazur Float Comp.	Firmed	5/7/18	1 pcs	0 pcs	1 pcs	\$225.00/pcs	\$225.00
	175052			Firmed	5/7/18	1 pcs	1/0 pcs	1 pcs	\$225.00/pcs	\$225.00
Sub Total:						2	0	2		\$450.00
2	175054	D350-636-012	Skidtube RH, Std Wearplates, DART (Apical) Cylindrical/Aerazur Float Comp.	Firmed	5/7/18	1 pcs	0 pcs	1 pcs	\$250.00/pcs	\$250.00
	175060			Firmed	5/7/18	1 pcs	1/0 pcs	1 pcs	\$250.00/pcs	\$250.00
Sub Total:						2	0	2		\$500.00
3	175817	D135-751-011	Skidtube with Standard Wearplates Fits LH or RH	Firmed	5/7/18	1 pcs	0 pcs	1 pcs	\$225.00/pcs	\$225.00
	175818			Firmed	5/7/18	1 pcs	1/0 pcs	1 pcs	\$225.00/pcs	\$225.00
Sub Total:						2	0	2		\$450.00
4	175481	D3391-023	Mid Tube Assembly	Firmed	5/7/18	1 pcs	0 pcs	1 pcs	\$0.00/pcs	\$0.00
Line Item Note RE-WORK <i>see PO039793</i>										
Grand Total:										\$1,400.00

Order Notes

Terms & Condition of Purchasing(Suppliers) and Procurement Quality Clauses are an integral part of our AS9100 requirements. To learn in detail, please visit www.dartaerospace.com for further explanation.